



Product description

Characteristics:

- Reduced labour costs
- Ready-to-use dispersion glue
- For gluing of structured fleece (pigmented and non-pigmented glass-fleece and cellulose-fleece) up to 220 g
- Special glue for glass fabrics in fine textures (natural white and pre-coated) up to 200 g
- No dilution and elaborate stirring necessary
- Use pure for application with roller, airless instrument or pasting machine
- Smooth application
- Perfect spreading
- Excellent gluing power
- Long open time during application
- Transparent when dry
- Preservative-free
- Free of solvents and harmful emissions

Material

Application Area:	For interior use on new and old solid undergrounds, such as mineral stucco, concrete, gypsum board (without lignin marks). Special adhesive for technical glass-fleece or cellulose-fleece, which should be painted over.
Binding Agent:	Special resin dispersion
Colour:	Colourless
Specific gravity:	1.02 g/cm ³
pH value:	Approx. 10
Diluting agent:	Water
Viscosity:	Slightly thixotropic

Technical data sheet

JONAS Vlieskleber



Application Characteristics

Application:	Brush / roller / spray (airless). Also recommended for use with wallpaper equipment.
Underground:	Needs to be clean, dry, and solid. Otherwise use JONAS Hydro-Haft-& Tiefgrund first to consolidate the underground. For underground treatment and application VOB, part C, DIN 18363 and the relevant BFS information must be observed.
Coating build-up:	<u>Roller:</u> without dilution. <u>Pasting machine:</u> use Vlieskleber without dilution. To find the ideal quantity of Vlieskleber, test with a piece of fleece. <u>Airless-spray:</u> dilution: use without dilution nozzle: 0.021 – 0.025 inch pressure: 150 – 200 bar filter: 60 Mesh
Spreading rate per coating:	Approx. 150 - 250 g/m ² .
Application temperature:	At least + 5°C (Degrees Celsius) for air and underground during application and drying.
Drying:	The surface of the coating is dry and can be painted over after 8 - 10 hours (at a temperature of 20 °C and a relative atmospheric humidity of 65 %). High humidity, low temperatures and low air exchange extend the hardening and drying time.
Cleaning of tools:	Clean with water immediately after use.

General information

Storage:	Cool, but not freezing.
Shelf-life:	Can be stored for at least 12 months after date of filling (see additional sticker) if stored properly in the unopened original packaging.
Art.No. and description:	42 25 001 JONAS Vlieskleber
Packaging:	16 kg
Ingredients:	Special resin dispersion, starch derivative, water, additives.
Preservative-free:	Preservative-free according to VdL guideline 01 or equivalent RAL DE-UZ102.
Safety:	Please follow the instructions of the safety data sheet.
Labelling:	This product is not classified according to EU regulation No 1272/2008 [CLP].
Waste disposal:	Empty containers can be disposed for recycling. Any dried residues of material can be disposed of as construction waste or together with domestic garbage. Containers with liquid material residues must be disposed of according to local regulations. For further information, please contact your local waste authority.
Advice acc. to CLP:	Keep out of reach of children. Wear appropriate respiratory protection (full mask / half mask equipped with filter type A2/P2). Avoid eating, drinking and smoking during use of the product. Ensure good ventilation during and after application. In case of contact with eyes or skin, rinse immediately with plenty of water. Do not empty into drains or water courses. Safety data sheet available on request.